

## ZX1 LASER MEASUREMENT SENSOR

with build-in Amplifier

Precise, Stable  
Easy displacement measurements



Highest performance is now available in matchbox size. Omron is defining a new class of measurement sensors using an advanced HSDR-CMOS (High Speed and Dynamic Range) camera chip.

### Features

- Stable measurement for objects with any surface
- Best in class performance for accuracy and speed
- Compact size for quick mounting
- Increased measurement range
- Simple configuration by one-button, Smart Tuning
- Reliable measurement in harsh environments
- Integrated display



## Specifications

	NPN output	ZX1-LD50A61 ZX1-LD50A66	ZX1-LD100A61 ZX1-LD100A66	ZX1-LD300A61 ZX1-LD300A66	ZX1-LD600A61 ZX1-LD600A66
	PNP output	ZX1-LD50A81 ZX1-LD50A86	ZX1-LD100A81 ZX1-LD100A86	ZX1-LD300A81 ZX1-LD300A86	ZX1-LD600A81 ZX1-LD600A86
<b>Measurement range</b>		50±10 mm	100±35 mm	300±150 mm	600±400 mm
<b>Light source (wave length)</b>		Visible-light semiconductor laser with a wavelength of 660 nm and an output of 1 mV max. JIS class 2, IEC/EN class 2, FDA class II <sup>*1</sup>			
<b>Beam size (Typical value) (Specified by the measurement center distance)<sup>*2</sup></b>		0.17-mm dia	0.33-mm dia	0.52-mm dia	0.56-mm dia
<b>Power supply voltage</b>		10 to 30 VDC, including 10% ripple (p-p)			
<b>Power consumption</b>		250 mA max. with power supply voltage of 10 VDC			
<b>Control output</b>		Load power supply voltage: 30 VDC max. load current: 100 mA max. (Residual voltage: 1 V max. for load current 10 mA max., 2 V max. for load current 10 to 100 mV)			
<b>Analog output</b>		Current output: 4 to 20 mA, Max. load resistance: 300 Ω			
<b>Indications</b>		Output, zero reset, Mode, laser ON, Smart Tuning			
<b>Response time</b>	<b>Judgement outputs</b>	Super-high-speed mode: 1 ms; High-speed mode: 10 ms; Standard mode: 100 ms			
	<b>Laser OFF input</b>	200 ms max.			
	<b>zero reset input</b>	200 ms max.			
<b>Temperature characteristic<sup>*3</sup></b>		0.03%F.S./°C			0.04%F.S./°C
<b>Linearity<sup>*4</sup></b>		±0.15%F.S.		±0.2%F.S.	±0.4%F.S. ±0.2%F.S. (200-600 mm)
<b>Resolution<sup>*5</sup></b>		2 μm	7 μm	30 μm	80 μm
<b>Ambient illumination</b>		Incandescent lamp: 7,500 lx max. (on light receiving side)		Incandescent lamp: 5,000 lx max. (on light receiving side)	
<b>Ambient temperature</b>		Operating: -10 to +55°C, Storage: -15 to +70°C (with no icing or condensation)			
<b>Ambient humidity</b>		Operating and storage: 35% to 85% (with no condensation)			
<b>Dielectric strength</b>		1,000 VAC, 50/60 Hz for 1 min			
<b>Vibration resistance</b>		10 to 55 Hz, 1.5-mm double amplitude, each in X, Y, and Z directions			
<b>Shock resistance</b>		500 m/s <sup>2</sup> , 3 times each in X, Y, and Z directions			
<b>Degree of protection<sup>*6</sup></b>		IEC50529, IP67			
<b>Connection method</b>		Prewired (standard cable length: 2 m); connector connection (standard cable length: 500 mm)			
<b>Weight (Packed state/Unit only)</b>	<b>Prewired (2 m)</b>	Approx. 240 g/Approx. 180 g		Approx. 270 g/Approx. 210 g	
	<b>Connector (500 mm)</b>	Approx. 170 g/Approx. 110 g		Approx. 200 g/Approx. 140 g	
<b>Materials</b>		Case and cover: PBT (polybutylene terephthalate), Optical window: Glass, Cable: PVC			
<b>Accessories</b>		Instruction sheet, Laser warning label (English)			

Note: False detection outside the measurement range can occur in the case of an object with high reflectance.

<sup>\*1</sup> Classified as Class 2 by EN60825-1 criteria in accordance with the FDA standard provisions of Laser Notice No.50. Notification to CDRH planned.

<sup>\*2</sup> Beam size: Defined as 1/e<sup>2</sup> (13.5%) of the central intensity at the smallest value of diameter for the measurement range (typical value)

False detections can occur in the case there is light leakage outside the defined region.

And the surroundings of the target object have a high reflectance in comparison to the target object.

<sup>\*3</sup> Temperature characteristic: Value for the case the space between the sensor head and Omron's standard target object is secured by an aluminum jig. (Measured at the measurement center distance)

<sup>\*4</sup> Linearity: indicates the error with respect to the ideal straight line of the displacement output in the case of measuring Omron's standard target object. Linearity and measured value may vary depending on target object.

<sup>\*5</sup> Resolution: Defined by setting in standard mode and executing Smart Tuning with Omron's standard target object (white ceramics).

Indicates the repetition accuracy for when the workpiece is in a state of rest. Not an indication of distance accuracy.

Resolution performance may not be satisfied in a strong electromagnetic field.

<sup>\*6</sup> Degree of protection is IP67 when the connector is connected to the extension cable.

Contact us for more information.

**OMRON EUROPE B.V.** Wegalaan 67-69, NL-2132 JD, Hoofddorp, The Netherlands. Tel: +31 (0) 23 568 13 00 Fax: +31 (0) 23 568 13 88 [www.industrial.omron.eu](http://www.industrial.omron.eu)

**Austria**  
Tel: +43 (0) 2236 377 800  
[www.industrial.omron.at](http://www.industrial.omron.at)

**Finland**  
Tel: +358 (0) 207 464 200  
[www.industrial.omron.fi](http://www.industrial.omron.fi)

**Italy**  
Tel: +39 02 326 81  
[www.industrial.omron.it](http://www.industrial.omron.it)

**Portugal**  
Tel: +351 21 942 94 00  
[www.industrial.omron.pt](http://www.industrial.omron.pt)

**Sweden**  
Tel: +46 (0) 8 632 35 00  
[www.industrial.omron.se](http://www.industrial.omron.se)

**Belgium**  
Tel: +32 (0) 2 466 24 80  
[www.industrial.omron.be](http://www.industrial.omron.be)

**France**  
Tel: +33 (0) 1 56 63 70 00  
[www.industrial.omron.fr](http://www.industrial.omron.fr)

**Netherlands**  
Tel: +31 (0) 23 568 11 00  
[www.industrial.omron.nl](http://www.industrial.omron.nl)

**Russia**  
Tel: +7 495 648 94 50  
[www.industrial.omron.ru](http://www.industrial.omron.ru)

**Switzerland**  
Tel: +41 (0) 41 748 13 13  
[www.industrial.omron.ch](http://www.industrial.omron.ch)

**Czech Republic**  
Tel: +420 234 602 602  
[www.industrial.omron.cz](http://www.industrial.omron.cz)

**Germany**  
Tel: +49 (0) 2173 680 00  
[www.industrial.omron.de](http://www.industrial.omron.de)

**Norway**  
Tel: +47 (0) 22 65 75 00  
[www.industrial.omron.no](http://www.industrial.omron.no)

**South Africa**  
Tel: +27 (0)11 579 2600  
[www.industrial.omron.co.za](http://www.industrial.omron.co.za)

**Turkey**  
Tel: +90 212 467 30 00  
[www.industrial.omron.com.tr](http://www.industrial.omron.com.tr)

**Denmark**  
Tel: +45 43 44 00 11  
[www.industrial.omron.dk](http://www.industrial.omron.dk)

**Hungary**  
Tel: +36 1 399 30 50  
[www.industrial.omron.hu](http://www.industrial.omron.hu)

**Poland**  
Tel: +48 (0) 22 645 78 60  
[www.industrial.omron.pl](http://www.industrial.omron.pl)

**Spain**  
Tel: +34 913 777 900  
[www.industrial.omron.es](http://www.industrial.omron.es)

**United Kingdom**  
Tel: +44 (0) 870 752 08 61  
[www.industrial.omron.co.uk](http://www.industrial.omron.co.uk)