

**Product Discontinuation  
Notices**

Issue Date  
July 12, 2024

MI-Z-2407099A

**Product Discontinuation**

Basic Switch

**Z-15H2-A4-K1**



**Recommended Replacement**

Basic Switch

**Z-15G-A4-K1**

**[ Final order entry date ]**

The end of September 2025

**[ Date of The Last Shipping ]**

The end of November 2025

**[ Caution on recommended replacement ]**

The operating ratings are different.

**[ Difference from discontinued product ]**

Recommended replacement Model	Body Color	Dimensions	Wire connection	Mounting Dimensions	Characteristics	Operation ratings	Operation methods
Z-15G-A4-K1	**	**	**	**	**	--	**

\*\* : Compatible

\* : The change is a little/Almost compatible

-- : Not compatible

- : No corresponding specification

**[ Operation ratings ]**

Product discontinuation Model Z-15H2-A4-K1		Recommendable replacement Model Z-15G-A4-K1	
Operating Force (OF)	: 1.96 ~ 2.50 N	Operating Force (OF)	: 2.45 ~ 3.43 N
Pretravel (PT)	: 0.3 mm MAX.	Pretravel (PT)	: 0.4 mm MAX.
Movement Differential (MD)	: 0.005 ~ 0.008 mm	Movement Differential (MD)	: 0.05 mm MAX.
Overtravel (OT)	: 0.1 mm MIN.	Overtravel (OT)	: 0.13 mm MIN.

Specifications and prices in this product news are as of the issue date and are subject to change without notice.

Only main changes in specifications are described in this document. Please be sure to read the relevant catalogs, datasheets, product specifications, instructions, and manuals for precautions and necessary information when using products.

